

Diesel Generating Set

PP175C

MODEL	PP175C
Standby Power (50Hz)	140KW / 175KVA
Prime Power (50Hz)	128KW / 160KVA

Standard Features

General Features:

Engine (DCEC Cummins 6CTA8.3-G1)

Radiator 50°C max, fans are driven by belt, with safety guard

24V charge alternator

Alternator: single bearing alternator IP23, insulation class H/H

Absorber

Dry type air filter, fuel filter, oil filter

Main line circuit breaker

Standard control panel

Two 12V batteries, rack and cable

Ripple flex exhaust pipe, exhaust siphon, flange, muffler

User manual



PHOTO FOR REFERENCE ONLY

Generator Ratings

Voltage	HZ	Phase	P.F (COS ϕ)	Standby Amps	Standby Ratings (KW/KVA)	Prime Ratings (KW/KVA)
440/254	50	3	0.8	230	140/175	128/160
415/240	50	3	0.8	243	140/175	128/160
400/230	50	3	0.8	253	140/175	128/160
380/220	50	3	0.8	266	140/175	128/160

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

Diesel Generating Set

PP175C

ENGINE DATA

Manufacturer / Model:	DCEC Cummins 6CTA8.3-G1, 4-cycle
Air Intake System:	Turbo, Water/Air Cooling
Fuel System:	PB type fuel pump
Cylinder Arrangement:	6 in line
Displacement:	8.3L
Bore and Stroke:	114*135 (mm)
Compression Ratio:	17.3:1
Rated RPM:	1500rpm
Max. Standby Power at Rated RPM:	180KW/241HP
Governor Type:	Mechanical

Exhaust System

Exhaust Gas Flow:	34.7m ³ /min
Exhaust Temperature:	570°C
Max Back Pressure:	10kPa

Air Intake System

Max Intake Restriction:	6kPa
Burning Capacity:	12.4m ³ /min
Intake Flow:	238m ³ /min

Fuel System

100% (Prime Power) Load:	215 g/kWh
75% (Prime Power) Load:	211 g/kWh
50% (Prime Power) Load:	216 g/kWh
100% (Prime Power) Load:	35.1L/h

Oil System

Total Oil Capacity:	23.8L
Oil Consumption:	≤4g/kwh
Engine Oil Tank Capacity:	15.1~18.9L
Oil Pressure at Rated RPM:	276-414kPa

Cooling System

Total Coolant Capacity:	34L
Max Water Temperature:	104°C

Diesel Generating Set***PP175C*****ALTERNATOR SPECIFICATION****GENERAL DATA**

Compliance with GB755, BS5000, VDE0530, NEMAMG1-22, IED34, CSAC22 and AS1359 standards.

Alternator Data

Number of Phase:	3
Connecting Type:	3 Phase and 4 Wires, "Y" type connecting
Number of Bearing:	1
Power Factor:	0.8
Protection Grade:	IP23
Altitude:	≤1000m
Exciter Type:	Brushless, self-exciting
Insulation Class, Temperature Rise:	H/H
Telephone Influence Factor (TIF):	<50
THF:	<2%
Alternator Capacity:	160KVA
Alternator Efficiencies:	92.3%

GENERATING SET DATA

Voltage Regulation:	≥±5%
Voltage Regulation, Stead State:	≤±1%
Sudden Voltage Warp (100% Sudden Reduce):	≤+25%
Sudden Voltage Warp (Sudden Increase):	≤-20%
Voltage Stable Time (100% Sudden Reduce):	≤6S
Voltage Stable Time (Sudden Increase)	≤6S
Frequency Regulation, Stead State:	≤5%
Frequency Waving:	≤0.5%
Sudden Frequency Warp (100% Sudden Reduce):	≤+12%
Sudden Frequency Warp (Sudden Increase):	≤-10%
Frequency Recovery Time (100% Sudden Reduce):	≤5S
Frequency Recovery Time (Sudden Increase):	≤5S

Diesel Generating Set

PP175C


Standard Features

- | | | |
|---|--|--|
| ◇ Standard Auto Control System | ◇ MCCB | ◇ Special tool for Cummins engine |
| ◇ Base Fuel Tank | ◇ Oil Drain Valve | ◇ One set of fuel filter / oil filter / belt |
| ◇ Starting batteries (Maintenance-Free & Watering-Free) with connective wires | ◇ Exhaust System (including until muffler) | ◇ Documents |

Options

- | | | |
|---------------------|-----------------------------------|-----------------------------|
| ◇ Daily Fuel Tank | ◇ Permanent Magnet Generator(PMG) | ◇ Remote Control Panel |
| ◇ Battery Charger | ◇ Rainproof Type | ◇ Automatic Transfer Switch |
| ◇ Engine Heater | ◇ Soundproof Type | ◇ Switch box |
| ◇ Alternator Heater | ◇ Trailer Type | ◇ Paralleling System |
| ◇ Water Separator | ◇ Spare Parts | |


Dimension & Weight



Open Type with Base Fuel Tank

Overall Size: 2430×945×1850 (mm)

Weight: 1720 kg



Soundproof Type

Overall Size: 3250×1170×1800 (mm)

Weight: 2485kg

Trailer Type


Overall Size: 4030×2140×2510 (mm)

Weight: 3430kg

Diesel Generating Set

PP175C

Auto Module Control Panel



Powergen Pacific Standard Control Panel uses micro processing technique integrating digital, intelligent and network techniques which can carry out functions including auto start/stop, data measure, alarming. The controller uses LCD display, optional Chinese and English display interface with operation easy and reliable. It can be widely used in all types of generator automatic control system for compact structure, advanced circuits, simple connections and high reliability. USB interface and ECU support CAN J1939.

Auto Parallel Control Panel



Automatic Parallel Control Panel This new automatic parallel system adopts intelligent modules, inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined together with the generator, which is very reliable. One generator, one panel. The panel can be used both for singly and parallel. It is only need to parallel generator with such panel when the capability needs to be enlarged in the future.

Sales Promises

Powergen Pacific provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: a, 15 months, counted on the day Powergen Pacific sold to the first buyer; b, One year after installation; c, 1000 running hours (accumulated); subject to the earlier one.

Service and parts are available from Powergen Pacific or distributors in your location.