

Diesel Generating Set

PP65C

| MODEL | PP65C |
|----------------------|--------------|
| Standby Power (50Hz) | 52KW / 65KVA |
| Prime Power (50Hz) | 48KW / 60KVA |

Standard Features

General Features:

Engine (DCEC Cummins 4BTA3.9-G2)

Radiator 50°C max, fans are driven by belt, with safety guard

24V charge alternator

Alternator: single bearing alternator IP23, insulation class H/H

Absorber

Dry type air filter, fuel filter, oil filter

Main line circuit breaker

Standard control panel

Two 12V batteries, rack and cable

Ripple flex exhaust pipe, exhaust siphon, flange, muffler

User manual



PHOTO FOR REFERENCE ONLY

Generator Ratings

| Voltage | HZ | Phase | P.F (COS φ) | Standby Amps | Standby Ratings (KW/KVA) | Prime Ratings (KW/KVA) |
|---------|----|-------|-----------------|-----------------|--------------------------------|------------------------------|
| 440/254 | 50 | 3 | 0.8 | 85 | 52/65 | 48/60 |
| 415/240 | 50 | 3 | 0.8 | 90 | 52/65 | 48/60 |
| 400/230 | 50 | 3 | 0.8 | 93 | 52/65 | 48/60 |
| 380/220 | 50 | 3 | 0.8 | 98 | 52/65 | 48/60 |

Prime Power (PRP): Prime power is available for an unlimited number of annual hours in variable load application, in accordance with GB/T2820 (eqv ISO8528) ; A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby Power Rating (ESP): The standby power rating is applicable for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

Diesel Generating Set***PP65C*****ENGINE DATA**

| | |
|----------------------------------|----------------------------------|
| Manufacturer / Model: | DCEC Cummins 4BTA3.9-G2, 4-cycle |
| Air Intake System: | Turbo, Water/Air DC |
| Fuel System: | AD type fuel pump |
| Cylinder Arrangement: | 4 in line |
| Displacement: | 3.9L |
| Bore and Stroke: | 102*120 (mm) |
| Compression Ratio: | 17.3:1 |
| Rated RPM: | 1500rpm |
| Max. Standby Power at Rated RPM: | 64KW/86HP |
| Governor Type: | Electronic |

Exhaust System

| | |
|----------------------|------------------------|
| Exhaust Gas Flow: | 9.9m ³ /min |
| Exhaust Temperature: | 560°C |
| Max Back Pressure: | 10kPa |

Air Intake System

| | |
|-------------------------|------------------------|
| Max Intake Restriction: | 6kPa |
| Burning Capacity: | 3.6m ³ /min |
| Air Flow: | 158m ³ /min |

Fuel System

| | |
|--------------------------|-----------|
| 100%(Prime Power) Load: | 212 g/kWh |
| 75%(Prime Power) Load: | 217 g/kWh |
| 50%(Prime Power) Load:: | 230 g/kWh |
| 100%(Prime Power) Load: | 13.5L/h |

Oil System

| | |
|----------------------------|----------|
| Total Oil Capacity: | 11L |
| Oil Consumption: | ≤4g/kwh |
| Engine Oil Tank Capacity: | 8.5~9.5L |
| Oil Pressure at Rated RPM: | 345kPa |

Cooling System

| | |
|-------------------------|-------|
| Total Coolant Capacity: | 24L |
| Max Water Temperature: | 100°C |

Diesel Generating Set

PP65C

ALTERNATOR SPECIFICATION

GENERAL DATA

Compliance with GB755, BS5000, VDE0530, NEMAMG1-22, IED34, CSAC22 and AS1359 standards.

Alternator Data

| | |
|-------------------------------------|--|
| Number of Phase: | 3 |
| Connecting Type: | 3 Phase and 4 Wires, "Y" type connecting |
| Number of Bearing: | 1 |
| Power Factor: | 0.8 |
| Protection Grade: | IP23 |
| Altitude: | ≤1000m |
| Exciter Type: | Brushless, self-exciting |
| Insulation Class, Temperature Rise: | H/H |
| Telephone Influence Factor (TIF): | <50 |
| THF: | <2% |
| Alternator Capacity: | 62.5KVA |
| Alternator Efficiencies: | 89.9% |

GENERATING SET DATA

| | |
|---|-------|
| Voltage Regulation: | ≥±5% |
| Voltage Regulation, Stead State: | ≤±1% |
| Sudden Voltage Warp (100% Sudden Reduce): | ≤+25% |
| Sudden Voltage Warp (Sudden Increase): | ≤-20% |
| Voltage Stable Time (100% Sudden Reduce): | ≤6S |
| Voltage Stable Time (Sudden Increase) | ≤6S |
| Frequency Regulation, Stead State: | ≤5% |
| Frequency Waving: | ≤0.5% |
| Sudden Frequency Warp (100% Sudden Reduce): | ≤+12% |
| Sudden Frequency Warp (Sudden Increase): | ≤-10% |
| Frequency Recovery Time (100% Sudden Reduce): | ≤5S |
| Frequency Recovery Time (Sudden Increase): | ≤5S |

Diesel Generating Set

PP65C


Standard Features

- ◇ Standard Auto Control System
- ◇ Base Fuel Tank
- ◇ Starting batteries (Maintenance-Free & Watering-Free) with connective wires
- ◇ MCCB
- ◇ Oil Drain Valve
- ◇ Exhaust System(including until muffler)
- ◇ Special tool for Cummins engine
- ◇ One set of fuel filter / oil filter / belt
- ◇ Documents

Options

- ◇ Daily Fuel Tank
- ◇ Battery Charger
- ◇ Engine Heater
- ◇ Alternator Heater
- ◇ Water Separator
- ◇ Permanent Magnet Generator(PMG)
- ◇ Rainproof Type
- ◇ Soundproof Type
- ◇ Trailer Type
- ◇ Spare Parts
- ◇ Remote Control Panel
- ◇ Automatic Transfer Switch
- ◇ Switch box
- ◇ Paralleling System


Dimension & Weight



Open Type with Base Fuel Tank

Overall Size: 1860×760×1380 (mm)

Weight: 980 kg



Soundproof Type

Overall Size: 2440×1060×1680 (mm)

Weight: 1450kg

Trailer Type


Overall Size: 3010×1640×2320 (mm)

Weight: 2100kg

Diesel Generating Set

PP65C

Auto Module Control Panel



Powergen Pacific Standard Control Panel uses micro processing technique integrating digital, intelligent and network techniques which can carry out functions including auto start/stop, data measure, alarming. The controller uses LCD display, optional Chinese and English display interface with operation easy and reliable. It can be widely used in all types of generator automatic control system for compact structure, advanced circuits, simple connections and high reliability. USB interface and ECU support CAN J1939.

Auto Parallel Control Panel



Automatic Parallel Control Panel This new automatic parallel system adopts intelligent modules, inserted and folded installed, no need the peripheral relay and logic circuit. The main switch adopts electronic breaker or frame breaker, combined together with the generator, which is very reliable. One generator, one panel. The panel can be used both for singly and parallel. It is only need to parallel generator with such panel when the capability needs to be enlarged in the future.

Sales Promises

Powergen Pacific provides a full line of brand new and high quality products. Each and every unit is strictly factory tested.

Warranty is according to our standard conditions: a, 15 months, counted on the day Powergen Pacific sold to the first buyer; b, One year after installation; c, 1000 running hours (accumulated); subject to the earlier one.

Service and parts are available from Powergen Pacific or distributors in your location.